

**SYNGEAR G2
GEAR OIL****PRODUCT DESCRIPTION:**

Syngear G2 is a premium, fully synthetic axle lubricant that is formulated with carefully selected base oils and performance additives. This ensures precise friction behavior and offers exceptional resistance to aging. Specifically designed for front-wheel drive gearboxes, this performance-optimized transmission oil minimizes torque loss and enhances the efficiency of the axle drive.

APPLICATION:

Syngear G2 is specifically formulated to meet the demanding requirements of BMW front axle transmissions. It is designed to minimize torque loss and increase the efficiency of the axle drive. It is important to adhere to the operating instructions provided by both the vehicle and transmission manufacturers to ensure optimal performance.

FEATURES & BENEFITS:

- Excellent viscosity/temperature properties
- Reduces running noise
- Outstanding corrosion protection
- Excellent wear resistance
- Very compatible with seals
- High pressure-absorption capability
- For extended oil-change intervals
- Excellent resistance to aging

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- BMW 83-22-2-413-511, API GL-5.

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SYNGEAR G2
			75W-85
KV@ 104°F /40°C	D7042	cSt	TBR
KV@212°F /100°C	D7042	cSt	12.0
Viscosity Index (min)	D2270	-	140
SP. Gravity @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.