



## BRAVOIL

# BRAVOIL™

### Technical Data Sheet

## ACTO 4 LV

### PRODUCT DESCRIPTION:

ACTO 4 LV is a premium Brake and Clutch Fluid that meets the latest ISO 4925 Class 6 standard. It has excellent low-temperature viscosity for improved performance in anti-locking systems and high-pressure systems. Additionally, its high wet boiling point extends its lifespan compared to traditional DOT 4 fluids.

### APPLICATION:

ACTO 4 LV brake fluid is recommended for use in vehicles that require ISO 4925 Class 6 specification and have hydraulic brake and clutch systems with ABS, ESP, and ASR. It can be mixed with DOT 3, DOT 4, and DOT 5.1 NON-SILICONE BASE products, but should not be mixed with silicone or mineral base fluids.

### FEATURES & BENEFITS

- Optimal ABS properties.
- Exception chemical stability.
- High lubricating power.
- Exceptional low viscosity at low temperature.
- Higher Dry and Wet boiling points.
- Miscibility with all brake fluids of the same specification.

### TYPICAL PROPERTIES:

P ARAMETERS	ACTO 4 LV
ISO	4925 Class 6
FMVSS 116	DOT 4
SAE	J 1704
MB	331.0
VW	501.14 (TL 766-Z)
FORD	WSS-M6C65-A2/M6C57-A2
BMW	QV 34001

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with brake fluid may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used brake fluid in to drains or the environment. Dispose to an authorized collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

### PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.