



BRAKE FLUID

BRAVOIL™

Technical Data Sheet

ACTO 4 PLUS HIGH-PERFORMANCE BRAKE FLUID

PRODUCT DESCRIPTION:

ACTO 4 Plus has been specially designed for use in heavy-duty brake systems of vehicles that require a DOT 4 synthetic brake fluid. The product is particularly recommended for brake systems with ABS. ACTO 4 Plus brake fluid can be mixed with all synthetic brake fluids of the same grade.

APPLICATION:

ACTO 4 Plus is specifically formulated for race vehicles and high-performance drivers, surpassing all DOT4 standards. It can be used alongside DOT3, DOT4, or DOT 5.1 fluids without any issues.

FEATURES & BENEFITS:

- High dry boiling point
- High wet boiling point
- High lubricating power
- Exceptional low viscosity at low temperature
- Miscibility with all brake fluids of the same specification

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- ISO 4925 Class 6
- FMVSS 116 DOT 4
- SAE J 1704
- MB 276.40

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	ACTO 4 PLUS
Kinematic Viscosity @100C	D445	cSt	2.1
Kinematic Viscosity @-40C	D445	cSt	1300
Boiling Point (Reflux)	D1120	°C	230
Wet Boiling Point	D1120	°C	180
Density at 15°C	D4052	g/ml	TBR

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with brake fluid may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used brake fluid in to drains or the environment. Dispose to an authorized collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.