



ELPRIMO ND 460

PRODUCT DESCRIPTION:

ELPRIMO ND 460 is made from Bentonite clay, highly refined heavy base oil, anti-oxidant, and anti-rust additives. It is resistant to water.

APPLICATIONS

ELPRIMO ND 460 grease is suitable for use within a very wide temperature range, especially at elevated temperatures for both industrial and automotive applications. The all-round properties make it suitable for various types of bearings, including temperature peaks up to 160°C.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 160°C
- Non-melting thickener keeps consistency at high temperature
- Good water resistance properties
- Good oxidation and thermal stability
- Suitable for heavy and shock loading capabilities
- Good corrosion and rust protection

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHODS | TYPICAL VALUE |
|--------------------------------|--------------|---------------------|
| NLGI Grade | - | 2 |
| Thickener Type | - | Bentone Clay |
| Base Oil Type | - | Mineral |
| Appearance | Visual | Smooth & Homogenous |
| Color | Visual | Brown |
| Work Penetration @25°C | ASTM D217 | 265-295 |
| Dropping Point °C, Min | ASTM D2265 | Non drop |
| Operating Temperature Range °C | INTERNAL | -20 to 160 |
| Base Oil Viscosity @40°C (Cst) | ASTM D445 | 460 |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.