



## FURIO PRO FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

FURIO PRO is a fully synthetic 4-stroke engine oil specifically created to provide outstanding performance and protection in motorcycle engines, especially under extreme driving conditions. Its formulation includes a specially designed low traction coefficient synthetic ester base oil, which effectively reduces internal frictional losses in the engine, resulting in improved performance. With this oil, users can expect increased power, ultimate engine protection, and enhanced wet clutch performance for smooth shifting and maximum power transfer.

### APPLICATIONS:

FURIO PRO oil is highly recommended for both air-cooled and water-cooled four-stroke motorcycle engines, particularly those used in Motocross and Enduro bikes, Quads, and Snowmobiles, regardless of whether they have a wet clutch or not. It is worth noting that FURIO PRO oil was previously known as Rush 4T Ester.

### FEATURES & BENEFITS:

- Excellent wear protection
- High shear stability and viscosity retention
- Excellent wet clutch compatibility
- High film strength for optimum lubrication

### PERFORMANCE LEVELS: Meets or Exceeds:

- API SN
- JASO MA2

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	FURIO PRO			
			5W-40	10W-50	10W-60	15W-50
Grade			5W-40	10W-50	10W-60	15W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	15.5	20.5	25.5	20.5
Viscosity Index (min)	D2270	-	160	145	145	135
SP. Gravity @15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220
Pour Point (max)	D97	°C	-39	-36	-36	-33
TBN	D2896	mg KOH/g	7	7	7	7
CCS	D5293	m.Pa.S	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-20°C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.