

**MOTO 4T ULTRA**
SYNTHETIC / SEMI SYNTHETIC / MINERAL**PRODUCT DESCRIPTION:**

Moto 4T Ultra is a multi-grade oil for four-stroke engines of motorcycles, scooters and mopeds. Moto 4T Ultra is blended by using high-quality base oils and the balanced additive system of quality additive manufacturers. It has improved detergency, antiwear, anti-foam properties and offers high resistance to oxidation and corrosion.

APPLICATION:

Moto 4T Ultra is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SG performance level, and also for motorbikes' transmissions and clutches, which need lubrication by motor oils.

FEATURES & BENEFITS:

- Maximum engine power.
- Unsuper passed gear protection.
- Outstanding wear protection
- Excellent shear and oxidation resistance
- Better clutch "feeling"
- Excellent low temperature fluidity

PERFORMANCE LEVELS: Meets or Exceeds:

- API SG
- JASO MA

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MOTO 4T ULTRA							
			5W-30	10W-30	10W-40	10W-50	15W-40	15W-50	20W-40	20W-50
Grade			5W-30	10W-30	10W-40	10W-50	15W-40	15W-50	20W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	11.7	15.1	19.5	15	19.5	15	20
Viscosity Index (min)	D2270	-	160	145	145	145	135	135	120	120
TBN	D8698	mgKOH/g	6	6	6	6	6	6	6	6
SP. Gravity @15°C/ 60°F	D4052	g/cm3	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-36	-36	-36	-33	-33	-24	-24

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.