



MOTO SUPER

PRODUCT DESCRIPTION:

Moto Super is formulated from high-quality base stocks and mixed with several additives with a stable thermal detergent system to improve engine cleanliness and durability. This lubricating oil serves to treat and reduce friction as well as provide protection for motorcycle engines. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without a wet clutch.

APPLICATION:

For scooters without wet clutch and where JASO MB specification is required.

FEATURES & BENEFITS:

- Contains Detergent Additive System with Thermal Stable to control deposit levels.
- Protects the engine from deposits optimally and the engine life increases longer.
- Has a high level of viscosity which makes the engine sound smoother.

PERFORMANCE LEVELS: Meets or Exceeds:

- API SL
- JASO MB

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MOTO SUPER	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F/40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F/100°C	ASTM D7042	cSt	11.9	14.0
Viscosity Index (min)	ASTM D2270	-	145	145
SP.Gravity @15°C/60 °F	ASTM D4052	g/cm3	TBR	TBR
Flash Point	ASTM D92	°C	220	220
Pour Point	ASTM D97	°C	-36	-36
TBN	ASTM D2896	mg KOH/g	7.0	7.0

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.