



REX LT

PRODUCT DESCRIPTION:

REX LT is a water-resistant calcium-soap thickened lubricating grease of NLGI 2 and NLGI 3 consistency. This is a good quality grease with excellent water resistance and good protection against corrosion.

APPLICATIONS

REX LT grease is well-suited for a variety of applications including the lubrication of nipples, spring leaves, chain drives, water pumps, non-bearing axles, and open and semi-open gear systems. Its water-resistant properties and corrosion protection make it an effective choice for these types of equipment and systems.

PRODUCT ADVANTAGES

- The operating temperature range is from -10°C to 60°C
- Very good lubricity
- Very good rust and corrosion protection
- Lower cost
- Excellent water washout properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE		
		1	2	3
NLGI Grade	-	1	2	3
Thickener Type	-	Calcium Soap		
Appearance	Visual	Smooth & Homogenous		
Color	Visual	Yellow		
Work Penetration @25°C	ASTM D217	310 - 340	265 - 295	220 - 250
Dropping Point °C, Min	ASTM D566	90	90	90
Operating Temperature Range °C	INTERNAL	-10 to 60		
Base Oil Viscosity @40°C (Cst)	ASTM D445	30 - 40		

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.