



S ULTRA 7000 SEMI SYNTHETIC

PRODUCT DESCRIPTION:

S ULTRA 7000 is a high-quality semi-synthetic engine oil that offers superior engine protection and helps prevent the accumulation of dirt and sludge. Formulated with highly refined base stocks and premium additive technology, this multi-grade oil is particularly beneficial for older engines operating in various driving conditions on highways and in the city. It provides excellent performance, ensuring the longevity and efficiency of the engine while reducing the risk of issues caused by deposits and build-up.

APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Excellent protection against sludge and varnish deposits

PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SJ/CF

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	S ULTRA 7000	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	11.6	15
Viscosity Index (min)	ASTM D2270	-	145	145
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-39	-39
TBN	ASTM D2896	mg KOH/g	6	6
CCS	ASTM D5293	m.Pa.S	<6600(-30°C)	<6600(-30°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.