

PCMO

Technical Data Sheet



S ULTRA B71 2312 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

S ULTRA B71 2312 is a high-performance reduced SAPS formula specifically designed for Peugeot and Citroën vehicles equipped with "Blue HDI" SCR diesel engines. This lubricant meets the B71 2312 specification required by these vehicles and also complies with the EURO 4, EURO 5, and EURO 6 pollution control standards. It effectively maintains the efficiency of the car exhaust Emission Reduction Systems in both diesel and gasoline-powered automobiles. With its fully synthetic base, it offers excellent thermal stability, wear protection, and prevents the formation of varnish and sludge to ensure engine cleanliness.

APPLICATION:

S ULTRA B71 2312 is the recommended lubricant for all Peugeot "Blue HDi" diesel engines and Citroën equipped with SCR systems. Additionally, the B71 2312 specification meets the requirements for the majority of gasoline engines and PSA - Peugeot Citroën HDi FAP Diesel engines.

FEATURES & BENEFITS:

- Low SAPS formulation helps to prolong the life and maintains the efficiency of the Emission Reduction Systems in both Diesel and Gasoline powered engines.
- Help achieve fuel economy.
- Improved cold flow properties.
- Offers the best possible protection in its category against wear and clogging.
- Reduced environmental impact.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

| SAE GRADE | 0W-30 |
|-----------|----------|
| ACEA-16 | C2 |
| PSA | B71 2312 |

TYPICAL PROPERTIES:

| PARAMETERS | ASTM | UNIT | S ULTRA B71 2312 |
|------------------------------------|-------|----------|------------------|
| SAE Grades | | | 0W-30 |
| Kinematic Viscosity @ 104°F /40°C | D445 | cSt | TBR |
| Kinematic Viscosity @ 212°F /100°C | D445 | cSt | 10.1 |
| Viscosity Index (min) | D2270 | - | 160 |
| SP. Gravity @15°C/60°F | D4052 | g/cm³ | TBR |
| Flash Point (min) | D92 | °C | 220 |
| Pour Point (max) | D97 | °C | -39 |
| TBN | D2896 | mg KOH/g | 7 |
| CCS | D5293 | m.Pa.S | <6200 (-35°C) |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

48 Version: 01-2023 — inquiry@bravoil.ae bravoil.ae