



S ULTRA MSP

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

S ULTRA MSP is a high-quality motor oil specifically formulated for downsized engines that undergo high levels of stress and require maximum power output. This oil is designed to enhance fuel efficiency and reduce CO2 emissions, making it ideal for vehicles that prioritize fuel economy. S ULTRA MSP ensures optimal lubrication, excellent lubricating film stability, and minimal wear and deposits even under extreme loads. It is particularly well-suited for engines equipped with start/stop systems, delivering maximum performance with low fuel consumption.

APPLICATIONS:

S ULTRA MSP is recommended for both gasoline and diesel vehicles, making it versatile for a wide range of automobiles. It has been specially developed to meet the specific requirements set by manufacturers such as BMW, GM, Mercedes-Benz, Opel, and others. This ensures that the oil is tailored to meet the unique needs of these vehicles, providing optimal performance and protection.

FEATURES & BENEFITS:

- Outstanding engine cleanliness.
- Excellent high and low temperature behavior.
- Excellent wear protection.
- High shear stability.
- Fully compatible with turbochargers and catalytic converters.
- Optimum oil pressure under all operating conditions.
- Optimum stability to aging.
- Long engine service life.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-30	0W-30	0W-20
API	SN PLUS/ SP	SN PLUS/ SP	SN PLUS/ SP
ACEA 2016	C2	C2	C5
BMW	-	LL-12FE	LL-17 FE+
MB	229.61	229.61	229.71
OPEL	OV 040 1547	OV 040 1547	OV 040 1547
GM	-	-	DEXOS D
LAND ROVER	-	-	STJLR.03.5006

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA MSP		
			5W-30	0W-30	0W-20
Grade			5W-30	0W-30	0W-20
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	53.4	52.8	41.2
Viscosity Index (min)	D2270	-	160	160	150
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39
TBN	D2896	mg KOH/g	9	9	9
CCS	D5293	m.Pa.S	<6600 (-30°C)	<6600 (-35°C)	<6600 (-35°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.