



S ULTRA PLUS MINERAL

PRODUCT DESCRIPTION:

S Ultra Plus mineral oils are specially formulated with high-quality base stocks and advanced performance additives to provide excellent engine protection and performance in diverse operating conditions. These oils are ideal for high-performance gasoline engine cars featuring direct-injection, multi-valve, and turbo-charger technologies. It is a recommended choice for ensuring optimal engine performance in such vehicles.

APPLICATION:

This product is recommended for gasoline-fueled automobiles and light-duty trucks that require an API SN rating.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SN/CF
- ACEA A3/B3/B4
- MB 229.1
- VW 505 00

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA PLUS	
			15W-40	20W-50
Grade			15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15.1	19.9
Viscosity Index (min)	D2270	-	140	130
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-33	-24
TBN	D2896	mg KOH/g	10	10
CCS	D5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.