



S ULTRA PLUS SEMI SYNTHETIC

PRODUCT DESCRIPTION:

S Ultra Plus is a highly advanced semi-synthetic engine oil that is specifically developed to provide exceptional engine protection and improved fuel economy. It meets the latest industry standards for "Full SAPS" passenger car lubricants and offers superior performance compared to conventional oils. The formulation of these oils is designed to deliver better oxidation resistance, deposit protection, wear protection, and optimal performance at low temperatures throughout the lifespan of the oil.

APPLICATION:

This engine oil is specifically recommended for gasoline-fueled automobiles and light-duty trucks that require an API Service Category SN/CF. It is formulated to meet the stringent requirements of this service category, ensuring optimal performance and protection for these vehicles.

FEATURES & BENEFITS:

- Outstanding wear protection under a wide variety of operating conditions
- Special cleaning additive to help prevent the formation of sludge and harmful deposits
- Optimal engine operating temperature, owing to thermal control formula
- Limits formation of deposits on the most loaded engine parts
- Provides safe operation of catalytic exhaust converters
- Resistant to extreme thermal load, due to high quality of base oil
- Enables fast and easy start in extreme temperature conditions
- Extra cleaning performance

PERFORMANCE LEVELS /MEETS OR EXCEEDS:

This product is recommended for use in applications requiring:

- API SN/CF
- ACEA A3/B3/B4
- MB 229.3/226.5
- Renault RN0700/RN0710

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA PLUS	
			10W30	10W40
Grade				
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.5	14.9
Viscosity Index (min)	D2270	-	145	145
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36
TBN	D2896	mg KOH/g	10	10
CCS	D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.