

РСМО

BRAVOIL

Technical Data Sheet

S ULTRA PREMIUM

PRODUCT DESCRIPTION:

S ULTRA PREMIUM oil is crafted using high-quality base stocks and advanced performance additives to ensure that your engine receives the protection and performance it needs in various operating conditions. This oil is specifically designed to offer enhanced oxidation resistance, deposit protection, wear protection, and low-temperature performance throughout the entire lifespan of the oil. With S ULTRA PREMIUM oil, you can trust that your engine will have the longevity and efficiency you desire, even in demanding circumstances.

APPLICATIONS:

S ULTRA PREMIUM oil is highly recommended for use in both naturally aspirated and turbocharged gasoline engines found in passenger cars and light commercial vehicles. It is also suitable for use in four-stroke gasoline engines and portable power equipment. This versatile oil is designed to provide optimal performance and protection for a wide range of gasoline engine applications, ensuring reliable operation and efficiency in various vehicles and equipment.

FEATURES & BENEFITS:

- "Viscous" formula well-suited to long stays in hot countries (20W for example)
- Particularly recommended for urban driving
- · Resistant to extreme thermal load due to high quality of
- base oil
- · Protects engines against deposits
- · Standard drain interval

PERFORMANCE LEVELS: Meets or Exceeds:

- API SM/CF
- ACEA A3/B3

- VW 501. 01 / 505.00
- RN 700, RN 710

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	S ULTRA PREMIUM	
Grade			15W40	20W50
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	15	20
Viscosity Index (min)	ASTM D2270	-	135	120
SP. Gravity @15°C/60°F	ASTM D4052	g/cm³	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-33	-24
TBN	ASTM D2896	mg KOH/g	8	8
ccs	ASTM D5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ea

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60℃, exposed to hot sun or freezing conditions.

inquiry@bravoil.ae bravoil.ae Version: 01-2023