

Technical Data Sheet

РСМО



S ULTRA PREMIUM SEMI SYNTHETIC

PRODUCT DESCRIPTION:

S ULTRA PREMIUM is a high-quality semi-synthetic engine oil that is specifically developed to provide excellent engine protection and improved fuel economy. This oil offers an array of benefits, including enhanced oxidation resistance, superior deposit protection, superior wear protection, and exceptional low temperature performance throughout its lifespan. It is engineered to meet the demands of modern engines and ensure optimal performance and longevity.

APPLICATIONS:

This engine oil is highly recommended for a wide range of applications including naturally aspirated and turbocharged gasoline engines in passenger cars, light commercial vehicles, light truck gasoline engines, four-stroke gasoline engines, and portable power equipment. It is designed to meet the specific needs of these engines, offering optimal protection and performance for various types of vehicles and machinery.

FEATURES & BENEFITS:

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving

PERFORMANCE LEVELS: Meets or Exceeds:

- API SM/CF
- ACEA A3/B3
- VW 501.01 / 505.00
- RN 700, RN 710
- MB 229.3

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	S ULTRA PREMIUM	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	10.4	15.1
Viscosity Index (min)	ASTM D2270	-	145	145
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-36	-36
TBN	ASTM D2896	mg KOH/g	8	8
CCS	ASTM D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

- · Oil film able to withstand high operating temperatures
- Protects engines against deposits
- Standard drain interval