



S ULTRA STANDARD
FULLY SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

S ULTRA STANDARD is a lubricant that contains a metallo-organic anti-wear additive system, providing exceptional wear control for engines in any operating condition.

APPLICATIONS:

This engine oil is highly recommended for gasoline-fueled automobiles and light-duty trucks that require an oil meeting the API SN/CF specification.

FEATURES & BENEFITS:

- Excellent engine cleanliness
Engine protection under a wide variety of operating conditions
Optimum power & performance under most severe driving conditions
Fully compatible with all emission control devices and all gasoline grades
Helps reduce engine wear and corrosion

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

Table with 9 columns: SAE GRADES, 0W-20, 5W-20, 5W-30, 5W-40, 10W-30, 10W-40, 15W-40, 20W-50. Rows include API, ILSAC, ACEA, MB, VW, and RENAULT specifications.

TYPICAL PROPERTIES:

Table with 11 columns: PARAMETERS, TEST METHOD, UNIT, and 8 columns for S ULTRA STANDARD grades (0W-20 to 20W-50). Rows include Kinematic Viscosity, Viscosity Index, SP. Gravity, Flash Point, Pour Point, TBN, and CCS.

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment.

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.