



### SUBZERO PSI PSI-OAT COOLANT

**PRODUCT DESCRIPTION:**

SUBZERO PSI is a high-quality, pre-mixed coolant that is ready to use. It utilizes organic acid technology, as well as silicate and phosphate, to provide exceptional protection for the cooling system. Specifically designed to meet the demands of modern engines within the Volkswagen Group, SUBZERO PSI offers excellent corrosion protection and has a long performance life even under high thermal stress. It is an updated version of G13 coolant and is compatible with previous coolant types such as G12 and G12+. It can be safely mixed with all other VW coolants, including G11 and G13.

**APPLICATIONS:**

SUBZERO PSI is specifically formulated to meet the unique needs and requirements of modern engines within the Volkswagen Group. It is designed to provide optimal performance and protection for these engines, ensuring their smooth operation and longevity.

**FEATURES & BENEFITS:**

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Universal application at passenger cars and commercial vehicles.
- Anti-cavitation, preventing foam and the retention of air,
- ensuring the good performance of the pump.
- Prevents the buildup of deposits, keeping the cooling system clean.
- Long life service product

**PERFORMANCE LEVELS / MEETS OR EXCEEDS:**

- Bentley (TL-774-L)
- Audi (TL 774-L)
- Bugatti (TL 774-L)
- Deutz (DQC CC-14)
- Lamborghini (TL 774-L)
- Porsche (TL 774-L)
- Seat (TL 774-L)
- Skoda (TL 774-L)
- Volkswagen (VW) (TL774-L)
- AS 2108-2004
- ASTM D 3306
- ASTM D 4985
- BS6580:2010
- CUNA NC 956-16
- PN-C40007:2000
- SAE J1034
- ÖNORM V5123
- SANS 1251:2005
- China GB 29743-2013

**TYPICAL PROPERTIES:**

PARAMETERS	ASTM	UNIT	SUBZERO PSI
pH	D1278	cSt	8
Freezing Point	D1177	°C	-37
Boiling Point	D1120	cSt	110
Density at 15.5C	D4052	g/cm3	TBR

**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with antifreeze may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used antifreeze in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

**PROTECT THE ENVIRONMENT:**

Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.