



SUBZERO TYPE D READY TO USE COOLANT

PRODUCT DESCRIPTION:

SUBZERO TYPE D is a modern and ready-to-use antifreeze/coolant that is ethylene glycol-based. Notably, it is completely devoid of silicates, nitrites, amines, phosphates, and boron. With this composition, SUBZERO TYPE D offers advanced coolant protection without the inclusion of these additives.

APPLICATIONS:

SUBZERO TYPE D is recommended as a suitable coolant for a wide range of internal combustion engines, including those found in cars, trucks, construction machinery, agricultural tractors, and stationary engines. Its versatile application makes it a reliable coolant choice for these various engine types.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Excellent antifoaming properties.
- Anti-cavitation, preventing retention of air, ensuring the good performance of the pump.
- Prevents the buildup of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Renault/ RVI Type D
- AFNOR NF R 15-601
- BS 6580/5117
- ASTM D 3306
- SAE J 1034

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SUBZERO TYPE D
pH	D1278	cSt	8.3
Freezing Point	D1177	°C	-26
Boiling Point	D1120	cSt	111
Density at 15.5C	D4052	g/cm3	TBR

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with antifreeze may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used antifreeze in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.