



## **SYNGEAR EP**

### **EXTREME PRESSURE AUTOMOTIVE GEAR OIL**

**PRODUCT DESCRIPTION:**

Syngear EP is a fully synthetic lubricant specifically formulated for use in drive axles of General Motors vehicles that require oil to meet GM specifications 9986115. This oil is designed to provide enhanced performance and protection for the drive axles, ensuring optimal functioning and longevity of the vehicle.

**APPLICATION:**

Syngear EP is highly recommended as a service-fill lubricant for the drive axles of General Motors vehicles that specifically require a product meeting GM 9986115 specifications. This fully synthetic lubricant ensures superior performance and protection for the drive axles, meeting the stringent requirements set forth by General Motors for optimal operation and longevity of the vehicle.

**FEATURES & BENEFITS**

- Excellent viscosity/temperature properties
- Outstanding axle wear protection.
- outstanding corrosion protection
- excellent wear resistance
- Improved shear stability for a stable viscosity during use
- excellent resistance to aging

**PERFORMANCE LEVELS / MEETS OR EXCEEDS:**

- GM 9986115

**TYPICAL PROPERTIES:**

PARAMETERS	ASTM	UNIT	SYNGEAR EP
			<b>75W-90</b>
KV@ 104°F /40°C	D7042	cSt	TBR
KV@212°F /100°C	D7042	cSt	14.6
Viscosity Index (min)	D2270	-	140
SP. Gravity @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-45

**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

**PROTECT THE ENVIRONMENT:**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.