

AUTOMATIC TRANSMISSION FLUID



Technical Data Sheet

SYNTHPOWER 9G TRONIC 9 SPEED AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

Synthpower 9G Tronic is a top-of-the-line Automatic Transmission Fluid (ATF) designed specifically for modern 9-speed automatic transmissions. It utilizes advanced synthetic base oils and premium additives to deliver high performance and fuel efficiency. This ATF is ideal for both service replacements and new vehicles with fuel economy-optimized transmissions.

APPLICATION:

Synthpower 9G Tronic drive is highly recommended for the latest generation of Mercedes Benz 9-speed automatic transmissions (9G tronic). This advanced transmission offers smooth and efficient shifting, allowing for improved performance and fuel economy. Whether on long stretches of highways or navigating through city streets, the 9G-Tronic drive enhances the driving experience in Mercedes-Benz vehicles.

FEATURES & BENEFITS

- · High thermal and oxidative stability.
- · Improved lubricating
- Outstanding shear stabity
- · maximum reduction of fuel consumption, which reduces emission
- · Superior overall performance

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

MB 236.17

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SYNTHPOWER 9G TRONIC
KV@ 104°F /40°C	D7042	cSt	TBR
KV@212°F/100°C	D7042	cSt	4.2
Viscosity Index (min)	D2270	-	140
SP. Gravity @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	℃	200
Pour Point (max)	D97	℃	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.