



SYNTHPOWER MULTI

SYNTHETIC

PRODUCT DESCRIPTION:

Synthpower Multi is a high-quality synthetic ATF that is suitable for use in different types of vehicles from various regions. It offers excellent protection against corrosion and foam-building, as well as anti-oxidation and anti-wear properties. Utilizing advanced technology, Synthpower Multi also includes special friction modifiers for enhanced performance.

APPLICATION:

Synthpower Multi is specifically designed for modern automatic transmission systems, including those with slip lockup clutch. It is particularly recommended for use in automatic gearboxes of various car makers such as GM, Ford, Chrysler, Hyundai, Kia, Mitsubishi, Nissan, Ssangyong, Subaru, Toyota, BMW, Citroën, Fiat, Mercedes-Benz, Peugeot, and Renault. Additionally, it can also be used in older automatic gearboxes, torque converters, power steering systems, boats' reverse gears, hydrostatic transmissions, and mechanical and hydraulic systems where this type of fluid is recommended.

FEATURES & BENEFITS:

- Long fluid life and long transmission life
- Exceptional oxidation stability and resistance to chemical deterioration
- Excellent flow properties at low start-up temperatures and high operating temperatures
- Excellent protection against rust and corrosion

PERFORMANCE LEVELS: Meets or Exceeds:

- Acura ATF Z1 (except CVTs)
- Audi (VAG) Tip-tronic, G 052 025-A2, G 052 162 A1 / A2 / A6, G 052 990 A2, G 055 025 A2, G 055 005 A1 / A2 / A6
- BMW LT 71141, LA2634, ETL7045E, ETL8072B,
- Bentley # PY112995PA
- BMW LT 71141, LA2634, ETL7045E, ETL8072B
- Chrysler MS 7176, MS 7176D, MS 7176E, MS 9602, ATF+, ATF+2, ATF +3, ATF +4
- Citroën Z 000169756, # 9730 AC, #9735-EJ, JWS 3309
- Daimler ATF +3, ATF +4
- Fiat 9.55550-AV1, 9.55550-AV2, 9.55550-AV4
- Ford MERCON, MERCON V, MERCON SP
- General Motors GM DEXRON III G, III H, GM DEXRON II D, II E,
- Honda ATF Z1 (except CVTs), # 082000-9001, ATF DW-1 (except CVTs)
- Hyundai ReD1, SP II, SP III, ATF 9638, # 040000C905G
- Infiniti ATF FMS, MATIC S, MATIC D, MATIC-J, MATIC K, MATIC W
- Isuzu ATF Z1 (except CVTs), H50235, SCS
- Jaguar M1375.4, JLM 20237, JLM 20238, Jaguar Fluid 8432
- Kia ATF SP-III, ATF SP-3, ReD1, # UM040 CH020
- Land Rover M1375.4, # TYK500050, STC 4863
- Lexus ATF WS, ATF Type T-IV, JWS 3324, NWS 9638
- Maserati # 231603
- Mazda JWS 3317, ATF M-V, 6-sp AT, ATF F-1
- Mercedes Benz MB 236.3, MB 236.5, MB 236.7, MB 236.9, MB 236.10, MB 236.11, MB 236.12, A0019892203
- Mini ASW 3309, # 83 22 0 402 413
- Mitsubishi Diamond (USA) / Dia Queen PSF, ATF-PA, ATF-J2, ATF-J3, SP II, SP III, PSF 3, AYC Fluid
- Nissan ATF FMS, MATIC S, MATIC D, MATIC J, MATIC K, MATIC W, ATF D3M
- Peugeot Z 000169756, # 9730 AC, #9735-EJ, JWS 3309
- Porsche # 999.917.547.00 (A2), # 043 205 28
- Renault DP0, Elfmatic J6, Renaultmatic D2, Renaultmatic D3
- Rolls Royce PL 31493PA
- Saab JWS 3309, # 93 165 147
- Saturn T-IV, # 22686186
- Subaru # KO410Y0700, ATF HP, SKU: SOA868V9241
- Suzuki JWS 3314 / 3317 / 2384K
- Toyota ATF DIII, ATF WS, ATF Type T, Type T-II, Type T-III, Type T-IV, JWS 2312D, JWS 3309, JWS 3324, LF,



AUTOMATIC TRANSMISSION FLUID

BRAVOIL™

Technical Data Sheet

- Volvo # 97342, # 1161521, # 1161540, # 97340
- VW (VAG) G 052 025-A2, G 052 162 A1 / A2 / A6, TL 52 162, G 052 990 A2, G 055 025 A2, G 055 005 A1 / A2 / A6
- Aisin Warner JWS 3309, JWS 2312D, CLIP, FF ATF, AW-F21
- Allison C4, TES-295
- Jalos JASO 1A
- Jatco JF613E
- Voith G607 (H55.6335XX)
- ZF TE-ML 03D / 04D / 09 / 14A / 14B / 16L / 17C
- AML # 4G4319A509/AA/S
- Appoll oil ATF ReD1K
- Castrol Transmax J, Transmax Z
- Esso ATF LT 71141, JWS 3314
- Fuchs Rave ATF 4400, Rave 3353
- Idemitsu K17, ATF HP
- Mobil ATF 3309, ATF 3317
- Petronas Tutela GI-V, Tutela GI-VI, Tutela Transmission Force4
- Shell M-1375.4, LA 2634, ATF 3353, 3403(-M115)
- Texaco ETL 7045E, ETL 8072B, N402
- Total ATF H50235, Fluide AT 42
- ZF Lifeguard 5, # S671 090 170, Lifeguard 6, # S671 090 255

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SYNTHPOWER MULTI
Kinematic Viscosity @ 104°F / 40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F / 100°C	ASTM D7042	cSt	7.35
Viscosity Index (min)	ASTM D2270	-	140
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.